



JUPITER^{PRO} Pv 3000



MPPT SOLAR INVERTER

PRODUCT KEY FEATURES

- Output Power Factor 1.0
- Pure Sine Wave & High Voltage MPPT Solar Inverter
- Priority Setting For Grid/PV Usage
- Compatible To Mains Voltage Or Generator Power
- Auto Restart While AC Is Recovering
- Conformal Coating For Internal Boards
- Built-in Anti-Dust kit
- MPPT Solar Charger of 80 AMP



Rated Power	3000VA/3000W
INPUT	
Voltage	230 VAC
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)
OUTPUT	
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%
Surge Power	6000VA
Efficiency (Peak)	93%
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)
Waveform	Pure sine wave
BATTERY	
Battery Voltage	24 VDC
Floating Charge Voltage	27 VDC
Overcharge Protection	32 VDC
SOLAR CHARGER & AC CHARGER	
Solar Charger Type	MPPT
Maximum PV Array Open Circuit Voltage	450 VDC
Maximum PV Array Power	3000W
MPP Range @ Operating Voltage	30 ~ 400 VDC(30 ~ 60VDC with battery connected)
Maximum Solar Charge Current	100A
Maximum AC Charge Current	80A
Maximum Charge Current	100A
PHYSICAL	
Dimension, D x W x H (mm)	110 x 288 x 390
Net Weight (kgs)	7.2
Communication Interface	RS232/RS485/WIFI
ENVIRONMENT	
Humidity	5% to 95% Relative Humidity (Non-condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C

Product specifications are subject to change without further notice.